



# **Product Info**

Brand: AM-R Series UPC: 85339975083 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 9 lbs Carton Length: 10 in Carton Width: 15 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

Carton Height: 15 in

Material: ULTRAGUARD® Fiberglass reinforced polyester -

compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket

system

# **AM1226RH**

12"x12"x6" AM-R Series fiberglass wall mount enclosure assembly with raised 2-screw hinged cover

#### **Availability:**

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size Cover Type: Opaque Closure Type: 2-Screw

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features:
Installation Type:
Height: 12.14 in
Width: 12.14 in
Depth: 6.13 in
Usable Depth: 7.26 in
Volume: 903 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13;  $\underline{\text{File No. }}$   $\underline{\text{E120175}}$ 

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





WARNING - PROP 65
Click here for more information!