



Product Info

Brand: Empire Series
UPC: 85339972266
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 77 lbs
Carton Length: 16 in

Carton Width: 35 in Carton Height: 45 in

Country of Origin: United States of America **Color:** Gray (RAL 7035) with clear window

 $\begin{tabular}{ll} \textbf{Material:} ULTRAGUARD @ Fiberglass reinforced polyester-compression molded SMC box and cover with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with bonded clear \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 and \mathbb{R}^2 with \mathbb{R}^2 wit$

polycarbonate window

Additional Materials: Plated carbon steel internal hardware, 316 stainless steel external hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMEC363012TW

36"x30"x12" Empire Series fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel twist latch

Availability:

Made to order; For up-to-date delivery on this product,

please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: Wall Cabinets

Cover Type: Opaque with Viewing Window

Closure Type: Metal Twist Latch

Mounting Description: Molded flange

Box Features: Installation Type:

Height: 36.5 in **Width:** 30.5 in **Depth:** 12.03 in

Usable Depth: 12.48 in **Volume:** 15062 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place

polyurethane gasket system.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









Click here for more information!