

Incandescent Lampholders



Allied Moulded Product's lampholder line has been expanded to include five new models. These products were developed for the electrical contractor looking for basic and cost effective lampholders.

Lampholder Features

- UL® listed file #E68415
- Mounting slots accept 3-1/2" or 4" outlet boxes
- Lamp rated 660 Watts (max)
- Made of UV and heat resistant thermoset material
- Nickel-plated brass screw shell and includes corrosion resistant steel hardware
- Accepts most manufacturers bulb protective cages
- For use in non-corrosive, residential lighting applications as permitted by local code
- All models are individually polybagged

LH-11P Features

- Keyless medium base design
- 4-terminal screws
- Optional 7" wire leads (LH-11WP)

LH-12P Features

- 3' pull cord extension
- 2-terminal screws
- Optional 7" wire leads (LH-12WP)

LH-13P Features

- 3' pull cord extension
- · 2-terminal screws and a ground screw
- Grounded outlet 125VAC/15A



Incandescent Lampholders

Keyless Medium Base	Catalog Number	Component Description	Outside Diameter	UPC# 85399	Pkg. Qty.	Std. Pkg. Wt. (lb.)
	LH-11P*	Keyless lampholder, 660W/250V, 4 ter- minal screws	4-9/16	87000	48	13
	LH-11WP	Keyless lampholder with wire leads, 660W/250V	4-9/16	87001	48	13
Pull Chain	Catalog Number	Component Description	Outside Diameter	UPC# 85399	Pkg. Qty.	Std. Pkg. Wt. (lb.)
	LH-12P*	Lampholder, 660W/250V, 3' pull cord, 2 terminal screws	4-9/16	87002	48	14
	LH-12WP	Lampholder with wire leads, 660W/250V, 3' pull cord	4-9/16	87003	48	14
Pull Chain with Grounded Outlet	Catalog Number	Component Description	Outside Diameter	UPC# 85399	Pkg. Qty.	Std. Pkg. Wt. (lb.)
	LH-13P*	Lampholder, 660W/125V, 3' pull cord, grounded outlet (125VAC/15A)	4-9/16	87004	48	15
	* Indicates model shown in picture)us D	LAMP 3MHN	HOLDER

Lampholder Mounting and Wiring Features



LH-11P



LH-11WP



LH-1



All models accept various manufacturers' bulb protective cages.

LH-12P

LH-12WP

LH-13P

Allied Moulded Products, Inc., Bryan, OH 43506 • ph: 419-636-4217 • fax: 800-237-7269 • www.alliedmoulded.com

ALLIED MOULDED PRODUCTS, Inc.