



# PC213-N

3.5" dia. round fixture support box for use with

nonmetallic sheathed cable **Carton Quantity:** 50

Mounting Description: Nail-on with fetter ring nails

Box Type: Ceiling - Fixture

Box Features: Nails

Installation Type: New Work

Width: 3-1/2 in Depth: 2-13/16 in Volume: 21 cu in Fixture Rating: 50lbs

# **Product Info**

Brand: flexBOX UPC: 85339980117 UNSPSC: 39121316 Carton Weight: 12 lbs Carton Length: 19 in

Carton Width: 12 in Carton Height: 16 in

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners

**Box Diameter: 3.5** 

#### Features:

Machine tapped fixture holes

## **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

**Box Diameter: 3.5** 

Standards:

ANSI / UL 514C: File No. E30594



#### **Fire Classification:**

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

## Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5  $\frac{1}{2}$  inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)