



## 9369-FB

4" dia. round fan support box for use with nonmetallic sheathed cable

**Carton Quantity:** 25

**Closure Type:**

**Mounting Description:** Bottom mount

**Box Type:** Ceiling - Fan/Fixture

**Box Features:**

**Installation Type:** New Work

**Width:** 4 in

**Depth:** 1-3/4 in

**Volume:** 16 cu in

**Fan Rating:** 35lbs

**Fixture Rating:** 50lbs

## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339765004

**UNSPSC:** 39121316

**Carton Weight:** 12 lbs

**Carton Length:** 15 in

**Carton Width:** 11 in

**Carton Height:** 8 in

**Country of Origin:** United States of America

**Color:** Off white

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Polyvinyl chloride clamps, Plated carbon steel fasteners

**Box Diameter:** 4

## Features:

Fixture support bolts and nuts included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## Application:

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support)

**Box Diameter:** 4

**Standards:**

ANSI / UL 514C: [File No. E30594](#)



**LISTED**

## Fire Classification:

### Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

---