ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506



9343-SS

4 square inch electrical junction box for use with nonmetallic sheathed cable

Carton Quantity: 50

Mounting Description: Steel stud screws for use with non-load bearing studs 22 gauge or lighter

Box Type: Wall - Junction

Box Features: Screws

Installation Type: New Work

Height: 4-1/16 in

Width: 4-1/16 in

Depth: 2-1/2 in

Volume: 32.3 cu in

Product Info

Brand: fiberglassBOX

UPC: 85339103752

UNSPSC: 39121332

Carton Weight: 27 lbs

Carton Length: 22 in

Carton Width: 12 in

Carton Height: 14 in

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl chloride clamps

Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed “K” Clamps bulk packed

Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications – 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594

UL LISTED

Fire Classification:

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded’s CEYY.9379 (Outlet boxes and fittings classified for fire resistance)