



AM363612L3PT

36"x36"x12" Empire Series fiberglass wall mount enclosure assembly with hinged cover and stainless-steel 3-point latching handle

Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: Wall Cabinets

Cover Type: Opaque

Closure Type: 3-Point Handle

Mounting Description: Molded flange

Height: 36.25 in **Width:** 36.25 in **Depth:** 10.14 in

Usable Depth: 10.27 in **Volume:** 15348 cu in

Product Info

Brand: Empire Series
UPC: 85339994824
UNSPSC: 39121324
Carton Quantity: 1

Carton Weight: 58 lbs Carton Length: 15 in Carton Width: 35 in Carton Height: 45 in

Country of Origin: United States of America

Color: Gray (RAL 7035)

 $\textbf{Material:} \ \, \textbf{ULTRAGUARD} \, \textbf{\textit{\textbf{B}}} \ \, \textbf{\textit{\textbf{Fiberglass}}} \ \, \textbf{\textit{\textbf{reinforced}}} \ \, \textbf{\textit{\textbf{polyester}}} \, \textbf{\textit{\textbf{\textbf{-}}}}$

compression molded SMC box and Cover

Additional Materials: 316 stainless steel external 3-point latching handle, 316 stainless steel external hardware (hinges/latches/fasteners), EPDM Spring loaded gasket, Plated alloy steel bonding fastener, Plated carbon steel internal hardware

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a spring loaded gasket system.

Application:

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 4, and 4X; $\underline{\text{File No.}}$ E120175

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive





WARNING - PROP 65
Click here for more information!