



# **Product Info**

Brand: POLYLINE® UPC: 85339991304 UNSPSC: 39121324 Carton Quantity: 1 Carton Weight: 9 lbs Carton Length: 10 in Carton Width: 18 in Carton Height: 20 in Country of Origin: United States of America Color: Gray (RAL 7035) Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMP1648NLF

16"x14"x8" POLYLINE  $\circledast$  polycarbonate wall mount enclosure assembly with hinged cover and nonmetal snap latch

#### Availability:

For up-to-date delivery on this product, please contact us at 1-800-722-2679 or sales@alliedmoulded.com

Enclosure Type: JIC Size

Cover Type: Opaque

Closure Type: Nonmetal Snap Latch

**Mounting Description:** Nonmetal flange fastened to back side brass inserts

**Box Features:** 

Installation Type:

Height: 15.98 in

Width: 13.98 in

Depth: 7.81 in

Usable Depth: 8.27 in

Volume: 1968 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13;  $\underline{\rm File}$  No.  $\underline{\rm E120175}$ 

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



WARNING - PROP 65 Click here for more information!