



### Switch & Receptacle Box



	Catalog Number	Cubic Inch Wire Capacity	Component Description	Outside Dimensions (min flange dim.)			Wall Substrate	UPC#	Standard	Standard
				Depth	Width	Height	Offset	85339	Pkg. Qty.	Pkg. Wt.(lbs.)
	2302-HNKV2	37.0	"HN" hanger, Speed Klamps™ factory installed, knockouts	3-7/16	4 (5-1/4)	3-3/4 (5)	1 - 1 1/4	92711	6	5

Note: All dimensions are inches unless specified otherwise.

## **Round Fan & Fixture Support Box**



Catalog	Cubic Inch	Component	Outside Dimen (flange dim		Fan	Fixture	Ceiling Substrate	UPC #	Standard	Standard
Number	Wire Capacity	Description	Depth	Diameter	Rating (lbs)	Rating (lbs)	Offset	85339	Pkg. Qty.	Pkg. Wt. (lbs.)
9371-FRV	12.0	4" dia. pan fan box, ½" deep pan, Speed Klamps™ factory installed	2-7/8 overall	4 (5-1/4)	70	110	1/2 - 5/8	92705	24	9

Note: All dimensions are inches unless specified otherwise.

## Other Available Vapor Seal Products Include:

With innovative products designed for the electrical contractor, Allied offers a complete line of wall and ceiling boxes for use in energy efficient homes to aid in sealing up the exterior walls per construction methods outlined in 402.4 of the 2009 International Energy Conservation Code.

- Nail-on Wall Boxes
- Fan Boxes
- 3/0 and 4/0 Round Ceiling Boxes
- New Work Ceiling Bar Mount Boxes
- Single and Double Drywall Applications



Allied Moulded Products, Inc., Bryan, OH 43506 • ph: 800-722-2679 • fax: 800-237-7269 • www.alliedmoulded.com

# fiberglassbox"







## **New Vapor Seal Products:**

Two new fiberglassBox<sup>™</sup> products have been added to the extensive lineup of Allied Moulded Vapor Seal "Air-Sealed" electrical boxes: a 4/0 ceiling Fan/Fixture support box for single layer sheet rock and a 2-gang flush device wall box for double layer sheet rock application.



Scan for more information







#### Vapor Seal Product Line Features

- A. Patented (U.S. Patent #6,908,003 B2) flexible polyurethane flange available for sealing box to air/vapor barrier. Flange products "V" are for single drywall and "V2" are for double drywall applications.
- **B.** Bright common nails fit securely in specially designed supports and are angled for easy installation.
- C. Tapered and machine tapped device holes allow device screw to be started by hand and speed installation time with high torque screwdrivers.
- **D.** Cubic inch capacity clearly marked and easy for contractor and inspector to locate and identify.
- E. Proudly UL® listed.
- F. Knockouts on fiberglass boxes are complete, reducing drafts and easily removed with wire for no-tool installation.
- **G.** Leveling ribs position face of box parallel to wall surface.
- **I.** 2-Hour Fire Rated clearly marked for easy inspector identification.

J. Nonmetallic Speed "K" Klamps<sup>TM</sup> dependably secure wire in box.







