ISSUE DATE: .96 [24.26] 12.72 [323.09] .56 [14.30] → -10.71 [272.08] .81 [20.57] **←** .44 [11.20] 12.49 [317.29] 14.50 [368.30] 13.70 [347.99] 2.21 [56.03] OPENING SIZE HMI120 A-−.324 x 45° TYP. 4x 316 STAINLESS-STEEL HINGE PIN SECTION A-A -(2) EACH #10-32 BRASS INSERTS, AND 316 STAINLESS STEEL CAPTIVE COVER TAMPER PROOF SCREWS WITH RETAINING O-RING -5.38 [136.75] -2x 5.62 [142.87] 12.07 [306.47] 0 0 FIP POLYURETHANE GASKET— 2x .24 [6.11] 11.92 302.78 2x 4.39 [111.49]  $-10x \varnothing .23[5.78]$ 13.85 [351.68] .19[4.83] 2x 8.64 [219.44] SECTION B-B FIP POLYURETHANE GASKET 2x 12.79 [324.82] 13.03 [330.93] MOUNTING HOLE PATTERN HMI120 FRONT VIEW WITH COVER REMOVED MATERIAL:
BOX - INJECTION POLYCARBONATE
STANDARD COVER - INJECTED POLYCARBONATE
CLEAR COVER: INJECTED POLYCARBONATE NOTE: 1. DATA SUBJECT TO CHANGE 2. WILL FIT ALLIED MOULDED ENCLOSURE SIZES 16X14 AND LARGER Access-Indus CONFIDENTIAL

THIS MATERIAL IS OWNED BY THE ALLIED
MOULDED PRODUCTS COMPANY, IS DISCLOSED
IN CONFIDENCE, AND IS NOT TO BE REPRODUCED
OR DISTRIBUTED WITHOUT PRIOR WRITTEN
PERMISSION FROM ALLIED MOULDED PRODUCTS. AMHMI142CCHTP