ISSUE DATE: .56 [14.30] → ← 6.72 [170.69] → 3.99 [101.22] .87 [21.97] -OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS (4) POLYCARBONATE FEET .10 [2.54] **BACK VIEW** 6.50 [165.10] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS 4.09 [103.89] STEEL FLANGE AND **FEET SCREWS** 7.47 [189.68] 5.20 [131.98] STAINLESS STEEL 6.75 [171.44] HINGE PIN (2) EACH #10-32 BRASS INSERTS AND STAINLESS STEEL CAPTIVE COVER SCREWS (4) \emptyset .31 [7.95] -FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-→ 4.91 [124.65] < NEOPRENE → 4.81 [122.24] < **GASKET** - .13 [3.30] 6.04 [153.40] 4.81 [122.24] 4.25 [107.95] MUSEL PRINTING -(4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED

CLEAR COVER AND WINDOWS- POLYCARBONATE

WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.

AMU664H