ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] .87 [21.97] OPTIONAL BACK PANEL SHOWN (2) POLYCARBONATE FLANGES, (GLUED) 0.100 [2.54mm] TH'K- ALUMINUM 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS .10 [2.54] **BACK VIEW** 7.63 [193.79] 4.09 [103.89] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND 6.50 [165.10] **FEET SCREWS** 6.75 [171.44] SLOT 6.88 [174.74] 5.18 [131.47] -STAINLESS STEEL HINGE PIN MAX DIST (8) R.162 [4.102] **SLOT** DIST **FRONT VIEW** WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL 4.00 [101.60] STAINLESS STEEL LOCKABLE TWIST LATCH NEOPRENE → 4.81 [122.24] < **GASKET** LOCATED ON CENTER 6.04 [153.40] .13 [3.30] 4.81 [122.24] 4.25 [107.95] (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664TF THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE, AND IS NOT TO BE REPRODUCED OR DISTRIBUTED CLEAR COVER AND WINDOWS- POLYCARBONATE WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.